

ANGLE ROLLS

CE35, CE40 & ER60

CE35
Part# CE35



CE40MR3
Part# CE40MR3



ER60H3
Part# ER60H3



U.S. Patent
5,970,770; 6,173,598
MX Patent
209183

Features

- Bending speeds 20% faster than competitive machines
- Universal tooling set included with each machine
- Forged roll shafts precision ground and fitted for maximum performance and minimal deflection
- Heavy duty structure and rigid components for high section modulus ratings
- Reinforced engineered mainframe design proven to outperform competitive models
- Patented by Ercolina®; simultaneous downfeed and roll movement to minimize deformation
- Programmable touchpad controls with digital center roll positioning display
- 40H3 hydraulic machine with memory storage with eight (8) individual programs and unlimited passes
- Remote pendant with low voltage controls and foot pedal switch
- Threaded roll shafts with micrometric flange adjustment helps eliminate spacer usage
- Inline direct drive roll shaft system
- Optional Anti-twist correction system for angle iron "Leg In" applications

Dimensions & Specifications

Model	CE35	CE40MR3	CE40H3	ER60H3
Roll Shaft Diameter	40mm	40mm	40mm	40mm
Center Roll Positioning	Manual	Manual with patented torque multiplier	Hydraulic 10 Tons	Hydraulic 10 Tons
Pipe Capacity	1 1/4" Sch. 40	2" Sch. 40	2" Sch. 40	*2" Sch. 40
Angle Capacity	1 1/2" x 1 1/2" x 1/4"	2" x 2" x 1/4"	2" x 2" x 1/4"	*2" x 2" x 1/4"
Universal Tooling	Included - 6 5/8" O.D.	Included - 6 5/8" O.D.	Included - 6 5/8" O.D.	Included - 6 5/8" O.D.
Programming	NA	NA	NC - Touchpad	NC - Touchpad
Number of Programs	NA	NA	8	1
Shaft Speed	6 / 12 RPM	10 RPM	10 RPM	10 / 20 RPM
Distance between Shafts	10 5/8"	10 5/8"	10 5/8"	10 5/8"
Drive Motor	3/4 hp into planetary	1 1/2 hp into planetary	1 1/2 hp into planetary	1 1/2 hp into planetary
Operating Position	Horizontal or Vertical	Horizontal or Vertical	Horizontal or Vertical	Horizontal or Vertical
Angle Twist Correction	Optional	Optional	Optional	Optional
Foot Pedal Stand	Yes	Yes	Yes	Yes
Operating Voltage	220V 1ph	**220V or 440V 3ph	220V or 440V 3ph	220V or 440V 3ph
Height	59"	59"	50"	50"
Length	27 1/2"	39"	39"	39"
Width	25 1/2"	26"	26"	26"
Shipping Weight	480 lbs.	763 lbs.	850 lbs.	1039 lbs.

* Capacity based on mild steel with machine in "Low bending speed"

** Single phase machines available

Refer to **Page 30** for Bending Capacities